

# Steelforce Pro 670 Highline SLS / C-Foot

## Dual step, sit-stand, height electrically adjustable

Height (mm)	min. 615 / max. 1275
Stroke (mm)	660
Speed (mm/s)	39
Width (mm)	min. 1100 / max. 1700
Length of feet (mm)	736
Column size (mm)	60 x 90
Dynamic capacity (kg)	100
Noise dB(A)	<55
Power	220-240Vac
Plug type	Replaceable
Gross Weight (kg)	30

Legs, feet, top supports and crossbars made of powder-coated steel.  
Soft start & stop function.  
Spindle lifting system and low energy consumption.

### Surface colour T-Foot

Pure Silver	●	<b>Purchase code T-Foot</b>	SLS50W068003J4GB-9
Traffic White	○		SLS50W06800329GB-9
Jet Black	●		SLS50W06800390GB-9

### Surface colour C-Foot

Pure Silver	●	<b>Purchase code C-Foot</b>	SLS50X074003J4GB-9
Traffic White	○		SLS50X07400329GB-9
Jet Black	●		SLS50X07400390GB-9

### Packing dimension single unit

945 x 275 x 168 (LxWxH - mm)

### Packing dimension pallet (20 frames)

1140 x 1130 x 1060 (LxWxH - mm)

### Accessories

Please see the accessories section to personalise your height adjustable frame.



Tested according to IEC 60335-1 by Intertek.

Steelforce Pro 670 Highline SLS T-Foot



Steelforce Pro 670 Highline SLS C-Foot

